

FLAVIA® S350 TECHNICAL

- Drink Volume Per Cup:** 160ml approx. (standard drinks), 240ml approx. (cappuccino)
- Required Cup Volume:** 240ml (minimum)
- Brewing Time:** Between 28 and 32s (standard drinks), Between 70 and 80s (cappuccino)
- First Drink Availability:** 6 minutes
- Hot Tank Capacity:** 2.5 litres
- Filterpack Bin Capacity:** 24
- Brewer Weight:** 19.5 kg (standard brewer), 20.25 (pay brewer)
- Dimensions**
- Brewer:** 332mm wide x 480mm deep x 470mm high Note: The depth of the brewer is 515mm with the mains supply connected. A gap of 60mm is needed behind the plumbed brewer for the mains water supply pipework.
 - Filterpack Unit:** 346mm wide x 410mm deep x 470mm high, 12 selections and 276 drinks
 - Additional Module:** 85mm wide x 410mm deep x 470mm high, 3 selections and 69 drinks
 - Ancillaries Unit:** 105mm wide x 410mm deep x 470mm high
 - Cup Holder:** 110mm wide x 410mm deep x 45mm high, capacity of 150 cups
- Complete System:** 900mm wide x 480mm deep x 470mm high
Brewer, 12 selection filterpack unit, ancillaries unit, cup holder.
- Base Cabinet:** 730mm wide x 620mm deep x 900mm high
9 selection filterpack unit for use with base cabinets has 207 drinks capacity.
- Plumbed:** Mains drinking water supply requirements:
- Dynamic water pressure of 1 to 7 bar (15 to 100 psi)
 - Flow rate of at least 2 litres per minute
 - Water to be cold and sodium free
 - BS1010 15mm stopcock within 1 metre of brewer
- Unplumbed:** Cold water is poured into the brewer by hand.
Tank capacity is 7.6 litres.
- Power Supply:** 230V, 50 Hz, maximum 5 amps
Mains lead 2 metres long
- Power Consumption:** 1100 W Boiling mode, 75W Standby mode
- Payment System:** (Pay brewer only)
- Accepts: 1p, 2p, 5p, 10p, 20p, 50p, £1, £2 coins and Flavia® token.
 - No change given
 - Key operated free/pay switch

